



HotEdge Rail is the first and only UL Listed roof edge ice melt system in the U.S. The revolutionary NEW patent-pending HotEdge Rail is engineered to prevent icicles and ice dams from forming along the edge of most roof structures by compressing a 12-watt commercial-grade, self-regulating heat cable directly against the existing metal drip edge. HotEdge Rail fastens to the fascia beneath the metal drip edge of a roof, providing a containment system for the heat cable.

HotEdge Rail is designed for a fast, simple retrofit to existing roofs or for installation on new construction. The system requires no roof clips or penetration of the roof deck, and no modifications are necessary on most metal roof structures.

EXCLUSIVE FEATURES

SECURE: An engineered channel was developed to receive existing composite asphalt shingles

SIMPLE & FAST INSTALLATION: Simple design installs easily on all EXISTING asphalt composite shingle roofs

NEC Compliant: The engineered open raceway design conforms to the NEC (National Electrical Code) Article 426 and provides access for insertion, inspection and replacement

NO MODIFICATIONS: This one piece design requires no shingle cutting or removal. Avoids damaging or modifying existing roof shingles which saves time on installations to reduce overall cost of project

LESS HEAT TRACE CABLE NEEDED: The benefit of a direct heat transfer is less heat trace cable is needed to prevent ice dam and icicles formations on all roof edges

A "GREEN" SOLUTION: Less heat trace cable means lower energy costs. In fact, all HotEdge roof edge melt systems use at least 50% less heat trace cable than all other alternatives, i.e. zig zag and aluminum metal tracks

WARRANTY: Industry leading 10-year limited warranty against heat cable failures and manufacture defects assures a long service. Heat trace cable is protected from UV light and snow/ice shifts and slides

COLOR MATCH: Our expansive inventory and nationwide network allows HotEdge to best match existing roof or trim color



SPECIFICATIONS

MATERIAL SELECTION:

.021" Copper, 24 gauge Kynar 500 Steel or .032 Aluminum Kynar 500

COLOR:

Our expansive inventory and nationwide network allows HotEdge to best match existing roof or trim color

DIMENSIONS:

5' length with optional mounting slots and fasteners included

HEATING SYSTEM:

Commercial-grade 12-watt/ft UL Listed self-regulating heat cable

COMPONENTS:

HotEdge Rail, heat cable, screws and commercial-grade adhesive

ELECTRICAL REQUIREMENTS:

120VAC or 208-277VAC. NEC Article 426.28 requires 30mA ground fault circuit protection for roof ice melting systems

FB01215231C
B2



BE green. SAVE green.